



CUSHMAN®

TITAN® HD



**VERSATILE AND RELIABLE PERFORMANCE
FOR IMPROVED PRODUCTIVITY.**

The Cushman® Titan® HD has the versatility you need to get more work done. Equipped with a fully electric, zero-emissions drivetrain in either 36V or 48V configurations, the Titan features a payload capacity of up to 2,500 pounds. So, whether you are transporting personnel, materials or equipment, the Titan HD will make the job easier and improve workplace performance.

LET'S WORK.®

2500^{LB}
TOTAL LOAD
CAPACITY

2
PERSON
SEATING


36V/48V
ELECTRIC
DRIVETRAIN OPTIONS



CUSHMAN® TITAN® HD



SPACIOUS CARGO DECK



**SWING-OUT SIDE
BATTERY COMPARTMENT**

STANDARD BRAKE LIGHTS

OPTIONS & ACCESSORIES

- Foam Filled Tires
- Front and Rear Bumper
- Forward Motion Indicator
- Hard Cab (with or without Doors)
- Front Hydraulic Brakes
- Pintle Hitch (requires rear bumper)
- Clevis Hitch (requires rear bumper)
- Custom Color
- Headlights and Turn Signals



**COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY**

36V MODEL

48V MODEL

| BODY & CHASSIS | | |
|--------------------------|--|---|
| FRAME | Welded Steel w/ DuraShield™ Powder Coat | |
| BODY & FINISH | Diamond Plate Patterned. Poly Primer & Acrylic | |
| STANDARD COLOR | Safety Yellow | |
| DIMENSIONS | | |
| OVERALL LENGTH | 114.0 in (290 cm) | |
| OVERALL WIDTH | 44.5 in (113 cm) | |
| OVERALL HEIGHT | 47.0 in (119 cm) | |
| WHEEL BASE | 67.0 in (170 cm) | |
| WHEEL TRACK | 38.0 in (97 cm) Front / 37.0 in (94 cm) Rear | |
| GROUND CLEARANCE | 4.8 in (12 cm) | |
| CARGO DECK CAPACITY | 2200 lb (998 kg) | |
| CARGO DECK MATERIAL | Heavy Duty Plywood | |
| POWER | | |
| POWER SOURCE | 36V DC Series Wound | 48V DC Shunt Wound |
| HORSEPOWER (KW) | 8.0 hp (6 kW) @ 1600 rpm | 15.2 hp (11.3 kW) @ 1600 rpm |
| ELECTRICAL SYSTEM | 36V DC | 48V DC |
| BATTERY (QTY/TYPE) | Six, 6V Deep Cycle, Swing Out | Eight, 6V Deep Cycle, Swing Out |
| BATTERY CHARGER | 36V On-Board, Delta Q 120 VAC, UL & CSA | 48V On-Board, Delta Q 120V AC, UL & CSA |
| KEY OR PEDAL START | Pedal | |
| SPEED CONTROLLER | Solid State 400 Amp Rated | Solid State 400 Amp Precision Dr. Sys. |
| DRIVE TRAIN | Motor Shaft Direct Drive | |
| TRANSAXLE | Differential w/ Helical Gears | |
| GEAR SELECTION | Dash-Mounted Forward-Neutral-Reverse | |
| REAR AXLE RATIO | 14.76:1 | |
| PERFORMANCE | | |
| SEATING CAPACITY | 2-Person | |
| WEIGHT W/O BATTERIES | 1040 lb (472 kg) | 1225 lb (556 kg) |
| CURB WEIGHT | 1410 lb (640 kg) | 1720 lb (780 kg) |
| VEHICLE LOAD CAPACITY | 2500 lb (1134 kg) | |
| BED LOAD CAPACITY | 2200 lb (998 kg) | |
| TOWING CAPACITY | 4600 lb (2087 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 22 ft (6.7 m) | |
| SPEED | 13 mph ± 0.5 mph (21 kph ± 0.8 kph) | |
| STEERING & SUSPENSION | | |
| STEERING | Rack & Pinion | |
| SUSPENSION | Independent, Transverse Leaf Spring, Shocks (Front) Leaf Springs and Shock Absorbers (Rear) | |
| SERVICE BRAKE | Rear Wheel Mechanical Drum | |
| PARKING BRAKE | Hand-Operated Mechanical | |
| TIRES (FRONT & REAR) | 5.70 x 8 (Load Range C) | |

www.cushman.com

©2016 Textron Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82304-G3 (Rev. 01/2016)