

OSX



ELECTRIC 24 or 36 VOLT
3000 lbs. (1360 kg)

The all new CLARK OSX 15 has raised the bar for order selectors. High performance and best-in-class operator comfort combined with generous standard features positions this order selector above the competition.



STANDARD FEATURES

- **100% AC drive and hydraulic motors**
Greater speeds mean improved productivity. No Brushes. All motors are enclosed to keep dust and contaminants out.
- **Fully proportional Lift & Lower**
Stopping at the exact height when you want to means no more lost time and eliminates antiquated two speeds offered by competitors.
- **Standard 1-1/4" to 5" pallet clamp**
Now nearly every pallet can be used with this variable width clamp. Improving productivity by eliminating the need for a specific sized pallet.
- **4 Point operator stance with safety in mind**
Operators are safer and confident at higher lifting heights. Solid grab points when traveling, especially when starting and stopping.
- **Premium anti-fatigue floor mat**
The textured non-slip mat is oil resistant and offers best of class operator comfort. A comfortable operator is a more productive operator.

SPECIFICATIONS

Manufacturer's Designation		OSX 15
Load Capacity / Rated Load	lbs(kg)	3000 (1360)
Height Overhead Guard	in(mm)	89.4 (2270)
Width of Outriggers	in(mm)	40 (1016)
Wheelbase	in(mm)	57 (1448)
Outside Turning Radius	in(mm)	68.9 (1751)
Travel speed loaded / unloaded	mph(kph)	7.5 (12) / 7.5 (12)
Power Unit	std. (optional)	24 Volt (36 Volt)

CLARK[®]
THE FORKLIFT