

# PWX HWX



**ELECTRIC 24 VOLT  
WALKIE/RIDER LOW LIFT PALLET TRUCK**  
6000 / 8000 lbs.  
(2720 / 3630 kg)



## STANDARD SPECIFICATIONS

**30/40**

Manufacturer's Designation		HWX 30	HWX 40	PWX 30	PWX 40
Load Capacity	lbs(kg)	6000 (2720)	8000 (3630)	6000 (2720)	8000 (3630)
Height	in(mm)	32.39 (823)	32.39 (823)	32.39 (823)	32.39 (823)
Width (For small/large battery comp.)	in(mm)	36.0/32.0 (914/813)	36.0/32.0 (914/813)	36.0/32.0 (914/813)	36.0/32.0 (914/813)
Length to fork face (For small/large battery comp.)	in(mm)	32.8/38.8 (833/986)	32.8/38.8 (833/986)	28.27/34.27 (718/870)	28.27/34.27 (718/870)
Outside Turning Radius (For small/large battery comp.)	in(mm)	73.3/79.3 (1862/2014)	73.3/79.3 (1862/2014)	69.1/75.1 (1755/1908)	69.1/75.1 (1755/1908)
Travel speed loaded / unloaded	mph (kph)	6.4/8.4 (10.4/13.5)	6.1/8.4 (9.8/13.5)	3.3/4.0 (5.3/6.4)	3.1/4.0 4.9/6.4)
Power Unit		24 volt	24 volt	24 volt	24 volt

## STANDARD FEATURES

- Enclosed AC traction motor and control
- Electromagnetic brake
- 48" x 27" Forks
- AC control
- 24 Volt
- Heavy-duty undercarriage
- Two forms of regenerative braking
- Entry/exit rollers
- Diagnostic dash display
- Hour meter
- Battery discharge indicator with interrupt
- Selector for high or low travel speed range



For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at [www.clarkmhc.com](http://www.clarkmhc.com).