



PACKED WITH FEATURES. FOCUSED ON VALUE.

THE BOBCAT GC18S-9 IC CUSHION TIRE FORKLIFT

Heavy-duty performance. Low cost of ownership. The Bobcat® GC18S-9 IC cushion tire forklift elevates your operations with power, performance, durability and outstanding fuel efficiency.

Dependable Power

A proven industrial engine, the GCT GK25 LP delivers excellent low-noise performance with minimal vibration and maximum durability. Meets all CARB and EPA emissions regulations.

Superior Components

Large king pins and tapered roller bearings create a stronger axle. The angled rollers stand up to powerful side forces. Tapered roller bearings have an inner race that eliminates king pin wear.

Smooth, Quick Direction Changes

The transmission shift Pro-Tek allows operators to go from forward to reverse and back smoothly and seamlessly – without the need to make a complete stop. The drive axle also contains a convenient electronic parking brake.

Heavy-Duty Hydrostatic Steer Axle

With no mechanical connections between the steering wheel and steer axle, operators command quick-response, low-effort steering for ideal maneuverability and safety.

Hydraulic Steer Axle Mechanism

With no mechanical connections between the steering wheel and steer axle, the hydrostatic axle is robust and ready for the job. Fewer moving parts mean that there are fewer things that can fail, assuring maximum runtime.

Operator Comfort

With great legroom, low-effort inching and braking, a thick rubber floor mat that absorbs more vibration, plus a fully adjustable suspension seat, long days at work don't seem so long.

Excellent Visibility

The GC18S-9 has hydraulic hoses and mast chains that are strategically placed to enhance forward visibility.

Advanced Safety Features

With an electronic parking brake, safety lights, alarm, mirrors and maximized visibility throughout the mast – you get a well-rounded safety and productivity package with the GC18S-9.

| SPECIFICATIONS | GC18S-9 |
|------------------------------------|---|
| Capacity | 3500 lb. (1575 kg) |
| Load Center | 24.0 in. (610 mm) |
| System Voltage | 12V |
| Operator Type | Seated |
| Tire Type | Cushion |
| Wheels, Load/Caster (x=Drive) | 2x/2 |
| Total Service Weight | 6437 lb. (2920 kg) |
| Axle Load at Loaded (Front/Rear) | 8585 lb. (3872 kg) / 1352 lb. (632 kg) |
| Axle Load at Unloaded (Front/Rear) | 2350 lb. (1066 kg) / 4087 lb. (1854 kg) |
| Overhead Guard Height | 81.0 in. (2060 mm) |
| Wheelbase | 50.6 in. (1285 mm) |
| Tread Width Front | 31.0 in. (786 mm) |
| Tread Width Rear | 32.0 in. (814 mm) |
| Outside Turning Radius | 73.5 in. (1867 mm) |
| Tilt Angle Forward/Backward | 6°/8° |
| Fork Size (T x W x L) | 1.4 x 4.0 x 41.0 in. (35 x 100 x 1050 mm) |

For more information on model details, go to [Bobcat.com](https://www.bobcat.com)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2024 Bobcat Company. All rights reserved.



B-3074 (01/24)
EP-10M-0124-6673-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
[Bobcat.com](https://www.bobcat.com)



Bobcat®

One Tough Animal.



HEAVY LIFTING ABILITY WITH LIGHT COST OF OWNERSHIP

THE BOBCAT GC35S-9 IC CUSHION TIRE FORKLIFT

The Bobcat® GC35S-9 IC cushion tire forklift packs unbelievable performance and a wide range of essential, productivity-boosting features at an amazing value.

Excellent Visibility

The reinforced mast is carefully designed to optimize forward visibility.

Dependable Power Plant

With your choice of two high-performance engines, you'll have high power and maximum durability for every task. The Doosan Spec PSI option features an advanced ECU (electronic control unit) that integrates and coordinates critical functions for high performance. The Kubota® 3.8L engine provides stand-out performance with great durability, plus low vibration and noise.

Smooth, Quick Direction Changes

The transmission shift Pro-Tek allows operators to go from forward to reverse and back smoothly and seamlessly – without the need to make a complete stop. The drive axle also contains a convenient electronic parking brake.

Heavy-Duty Hydrostatic Steer Axle

With no mechanical connections between the steering wheel and steer axle, operators command quick-response, low-effort steering for ideal maneuverability and safety.

Superior Components

Large king pins and tapered roller bearings help to deliver a stronger axle. The angled rollers stand up to powerful side forces. Tapered roller bearings have an inner race that eliminates king pin wear.

Hydraulic Steer Axle Mechanism

The GC35S-9 steer axle design is industry proven and extremely durable, providing long life and lower operating costs.

Operator Comfort

With great legroom, low-effort inching and braking, a thick rubber floor mat that absorbs more vibration, plus a fully adjustable suspension seat, long days at work don't seem so long.

Advanced Safety Features

With an electronic parking brake, safety lights, alarm and mirrors, and maximized visibility throughout the mast, you get a well-rounded safety and productivity package with the GC35S-9.

| SPECIFICATIONS | GC35S-9 |
|------------------------------------|---|
| Capacity | 8000 lb. (3620 kg) |
| Load Center | 24.0 in. (600 mm) |
| System Voltage | 12V |
| Operator Type | Seated |
| Tire Type | Cushion |
| Wheels, Load/Caster (x=Drive) | 2x/2 |
| Total Service Weight | 13,470 lb. (6110 kg) |
| Axle Load at Loaded (Front/Rear) | 18,043 lb. (8184 kg) / 3427 lb. (1554 kg) |
| Axle Load at Unloaded (Front/Rear) | 4657 lb. (2112 kg) / 8813 lb. (3997 kg) |
| Overhead Guard Height | 84.8 in. (2155 mm) |
| Wheelbase | 61.8 in. (1570 mm) |
| Tread Width Front | 41.0 in. (1042 mm) |
| Tread Width Rear | 41.1 in. (1044 mm) |
| Outside Turning Radius | 90.5 in. (2298 mm) |
| Tilt Angle Forward/Backward | 5°/6° |
| Fork Size (T x W x L) | 2.0 x 5.9 x 47.2 in. (50 x 150 x 1200 mm) |

For more information on model details, go to [Bobcat.com](https://www.bobcat.com)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2024 Bobcat Company. All rights reserved.



B-3075 (01/24)
EP-10M-0124-6673-F

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078
[Bobcat.com](https://www.bobcat.com)



Bobcat®

One Tough Animal.